

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SILVERDREAM Prismatic H-50720
Product code : 022357RL068

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cosmetic products

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:
From outside US : (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free) : 1-800-5355-053

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

ethyl acetate
acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 607-022-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 50 - <= 100
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

	231-072-3 013-002-00-1 01-2119529243-45		
acetone	67-64-1 200-662-2 606-001-00-8	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.

Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.

If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.

Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
ABC powder
Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.2	02.10.2018	102000030597	Date of first issue: 02.10.2018

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

- Further information on : Protect from humidity and water.
-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

storage conditions

Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cosmetic products

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis (Version Date)
ethyl acetate	141-78-6	TWA	200 ppm	GB EH40 (2005-04-06)
		STEL	400 ppm	GB EH40 (2005-04-06)
		STEL	400 ppm 1,468 mg/m ³	2017/164/EU (2017-02-01)
Further information	Indicative			
		TWA	200 ppm 734 mg/m ³	2017/164/EU (2017-02-01)
Further information	Indicative			
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40 (2011-12-01)
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable)	4 mg/m ³	GB EH40 (2011-12-01)
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version
1.2

Revision Date:
02.10.2018

SDS Number:
102000030597

Print Date: 19.11.2018
Date of first issue: 02.10.2018

	and exposure to these must comply with the appropriate limit., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Inhalable)	10 mg/m ³	GB EH40 (2005-04-06)
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable)	4 mg/m ³	GB EH40 (2005-04-06)
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version
1.2

Revision Date:
02.10.2018

SDS Number:
102000030597

Print Date: 19.11.2018
Date of first issue: 02.10.2018

	exposure should be used			
		TWA (inhalable dust)	10 mg/m ³	GB EH40 (2011-12-01)
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
		TWA (Respirable dust)	4 mg/m ³	GB EH40 (2011-12-01)
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
acetone	67-64-1	TWA	500 ppm	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version
1.2

Revision Date:
02.10.2018

SDS Number:
102000030597

Print Date: 19.11.2018
Date of first issue: 02.10.2018

			1,210 mg/m ³	(2000-06-16)
Further information	Indicative			
		TWA	500 ppm 1,210 mg/m ³	GB EH40 (2005-04-06)
		STEL	1,500 ppm 3,620 mg/m ³	GB EH40 (2005-04-06)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ethyl acetate	Workers	Inhalation	short term – local effects	1468 mg/m ³
	Workers	Inhalation	short term – systemic effects	1468 mg/m ³
	Workers	Inhalation	long term – local effects	734 mg/m ³
	Workers	Skin contact	long term – systemic effects	63 mg/kg
	Workers	Inhalation	long term – systemic effects	734 mg/m ³
	Consumers	Inhalation	short term – local effects	734 mg/m ³
	Consumers	Inhalation	short term – systemic effects	734 mg/m ³
	Consumers	Inhalation	long term – local effects	367 mg/m ³
	Consumers	Skin contact	long term – systemic effects	37 mg/kg
	Consumers	Inhalation	long term – systemic effects	367 mg/m ³
	Consumers	Ingestion	long term – systemic effects	4.5 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	long term – local effects	3.72 mg/m ³
	Consumers	Oral	long term – systemic effects	3.95 mg/kg
acetone	Workers	Skin contact	long term – systemic effects	186 mg/kg
	Workers	Inhalation	long term – systemic effects	1210 mg/m ³
	Consumers	Ingestion	long term – systemic effects	62 mg/kg
	Consumers	Skin contact	long term – systemic effects	62 mg/kg
	Consumers	Inhalation	long term – systemic effects	200 mg/m ³
	Workers	Inhalation	short term – local effects	2420 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version
1.2

Revision Date:
02.10.2018

SDS Number:
102000030597

Print Date: 19.11.2018
Date of first issue: 02.10.2018

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Soil	0.148 mg/kg
	STP	650 mg/l
	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	Fresh water sediment	1.15 mg/kg
aluminium powder (stabilised)	Marine sediment	0.115 mg/kg
	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
acetone	Soil	29.5 mg/kg
	Fresh water	10.6 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine water	1.06 mg/l
	Marine sediment	3.04 mg/kg
	STP	100 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection

: Use suitable breathing protection if workplace concentration requires.

In the case of vapour formation use a respirator with an

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version
1.2

Revision Date:
02.10.2018

SDS Number:
102000030597

Print Date: 19.11.2018
Date of first issue: 02.10.2018

approved filter.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: silver
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 56 - 78 °C
Flash point	: -4 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Auto-ignition temperature	: No data available
Smoldering temperature	: No data available
Decomposition temperature	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

Relative vapour density : No data available
Relative density : No data available
Density : 1.08 g/cm³
Bulk density : No data available
Water solubility : No data available
Solubility in other solvents : No data available
Partition coefficient: n-octanol/water : No data available
Decomposition temperature : No data available
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available
Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

Oxidizing agents

10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : (Rat): 5,620 mg/kg
Acute inhalation toxicity : LC50 (Rat): 56 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

acetone:

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg
(Mouse): 3,000 mg/kg
(Rat): 9,800 mg/kg
Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version
1.2

Revision Date:
02.10.2018

SDS Number:
102000030597

Print Date: 19.11.2018
Date of first issue: 02.10.2018

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

acetone:

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Eye irritation

Components:

acetone:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethyl acetate:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

acetone:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT
IMDG : PAINT, CLASSIFIED ACCORDING TO 2.3.2.2 IMDG-CODE
IATA : Paint, classified according to 3.3.3.1 IATA-DGR

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction : 355

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version 1.2 Revision Date: 02.10.2018 SDS Number: 102000030597 Print Date: 19.11.2018
Date of first issue: 02.10.2018

(passenger aircraft)
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H228 : Flammable solid.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU : Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.2	02.10.2018	102000030597	Date of first issue: 02.10.2018

2000/39/EC / TWA : Limit Value - eight hours
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SILVERDREAM Prismatic H-50720

Version
1.2

Revision Date:
02.10.2018

SDS Number:
102000030597

Print Date: 19.11.2018
Date of first issue: 02.10.2018
